

4-20 Monitor

Centeron Wireless Tank Monitoring System

The Centeron 4-20 mA monitor is a simple, cost effective means to remotely monitor a variety of 4-20mA sensors including temperature, pressure, level, and flow.

- Easily interfaces with existing 4-20 loop systems
- Use with any 4-20mA sensor
- Low maintenance
- No calibration
- Eliminates costly electrical wiring

Specifications:


- Accuracy: +/- 0.5%
- Temperature range: -40C to +80C
- Nema 4X enclosure
- 5-year battery life with 4 hour transmit interval (sensor powered separately)
- Low battery indication
- Radio range: 1 mile line of sight, 500 feet obstructed
- Radio complies with FCC Part 15
- ETL/cETL listed: Intrinsically safe for use in Class I, Division 1, Group D hazardous locations

The Centeron System

We start with an easy to install monitor. It's wireless, so no special know-how or tools are needed. It's powerful, too. Our DSSS radio technology is far superior to the narrow bandwidth radios found in other wireless systems. That means you receive your data even in the harshest environments.




The monitor sends the tank level data to the controller. The



controller collects and manages the data then sends it to the Centeron Data Center. From there, you can retrieve your info anytime, wherever you are.

Just think about what that information can mean to your business. An up-to-date, accurate account of tank level allows you to deliver your product when it needs to be delivered. Centeron puts you in control so you can manage your business better.



Call 1-865-981-3118 and speak directly to a Robertshaw applications engineer.



Exceptional DSSS radio technology is superior to narrow band systems, resulting in more reliable communications. So advanced, it's already the recipient of 12 patents, with additional pending.

Centeron®

The World's No. 1 Wireless Tank Monitoring System



4-20 Monitor									
	0	6	0	60 Minute transmit interval					
	1	2	0	120 Minute transmit interval					
	2	4	0	240 Minute transmit interval					
				0	Loop power				
				B	Monitor battery power				
					0	80 mSec measurement time (standard)			
					1	1100 mSec measurement time			
P	M				E	O	O	O	
						0			F 9 N

ETL/cETL Marked Intrinsically Safe apparatus for use in Class I, Division 1, Group D hazardous locations, conforming to ANSI/UL 913 and CAN/CSA C22.2 No. 157.

FCC Part 15 Registered: NU9TX0625-0300

This device is manufactured by Robertshaw Controls Company, in Maryville, TN USA under the following US Patents: 4,977,577; 5,067,136; 5,119,396; 5,265,120; 5,408,217; 4,581,606; Patents pending in the US and other countries.

Robertshaw
Industrial Products

U.S.A. – Robertshaw Industrial Products
1602 Mustang Drive, Maryville, Tennessee 37801
Tel Sales: 800-237-7429 Technical Support: 865-981-3118
www.robertshawindustrial.com • www.centeron.net